

TECHNOLOGY OF FUEL CELLS AND BATTERIES

BTECH VII SEM
PROGRAM CORE ELECTIVE IV

TECHNOLOGY OF FUEL CELLS AND BATTERIES

Professional Core Elective – IV(1)

Instruction per week : [L-3, T -0] 3 Hours

Duration of SEE : 3 Hours

Credits : 3

CIE: 25 Marks

SEE : 75 Marks

COURSE OBJECTIVES

Students to learn

1. To introduce the fundamentals of fuel cells
2. To understand the fuel cell electrochemistry
3. To learn fuel cell process design
4. To understand electrochemistry of the various primary batteries.
5. To analyze applications of secondary batteries.

Unit-I: Overview of Fuel cells: what is a fuel cell, brief history, classification, how does it work, why do we need fuel cells, Fuel cell basic chemistry and thermodynamics, heat of reaction, theoretical electrical work and potential, theoretical fuel cell efficiency.

Unit-II: Fuels for Fuel Cells: Hydrogen, Hydrocarbon fuels, effect of impurities such as CO, S and others. Fuel cell electrochemistry: electrode kinetics, types of voltage losses, polarization curve, fuel cell efficiency, Tafel equation, exchange currents.

Unit-III: Fuel cell process design: Main PEM fuel cell components, materials, properties and processes: membrane, electrode, gas diffusion layer, bi-polar plates, Fuel cell operation conditions: pressure, temperature, flow rates, humidity. Fuel processing: Direct and in-direct internal reforming, reformation of hydrocarbons by steam, CO₂ and partial oxidation, Direct electro-catalytic oxidation of hydrocarbons, carbon decomposition, Sulphur tolerance and removal, Using renewable fuels for SOFCs.

Unit-IV: Batteries: Principles of operation, electrochemical principles and reactions battery electrolytes factors affecting battery performance. Primary batteries: introduction, Zinc-carbon batteries, Magnesium and Aluminum batteries, Lithium Primary batteries and Alkaline-Manganese batteries.

Unit-V: Secondary batteries: introduction, Lead-Acid batteries, Iron electrode batteries, industrial and aerospace Nickel-cadmium batteries and Lithium – Ion batteries and applications of batteries.

EXAMINATION: Part – A for 25 marks (with 10 questions: two question from each unit - Compulsory) and Part – B for 50 marks (5 questions to be answered out of 7 of equal weightage selecting at least one from each Unit).

COURSE OUTCOMES:

1. Understand the fuel cell fundamentals
2. Analyze the performance of fuel cell systems
3. Understand construction of fuel cell and operation conditions
4. Have a firm knowledge on the primary batteries.
5. Understand the applications of secondary batteries.

TEXT BOOKS

1. Hoogers., Fuel Cell Technology Hand Book, CRC Press, 2003.
2. Karl Kordesch & Gunter Simader, Fuel Cells and Their Applications, VCH Publishers, NY, 2001.
3. F. Barbir, PEM Fuel Cells: theory and Practice, 2nd ed, Elsevier/Academic Press, 2013.
4. Linden, D.; Reddy, T.B , Handbook of Batteries, McGraw-Hill, 2002
5. Ronald Dell, David Anthony James Rand, Understanding Batteries, Royal Society of Chemistry, 2001

REFERENCE BOOKS

1. Subhash C. Singal and Kevin Kendall, High Temperature Fuel Cells: Fundamentals, Design and Applications, 2003.
2. O'Hayre, R. P., S. Cha, W. Colella, F. B. Prinz, Fuel Cell Fundamentals, Wiley, NY 2006.

.....

FUEL CELL

- A fuel cell is an electrochemical device that converts the chemical energy from a fuel into electricity through a chemical reaction. Unlike traditional combustion engines that burn fuel and produce mechanical energy, fuel cells operate without combustion, making them more efficient and environmentally friendly.
- Here's how a fuel cell works:
- **Fuel Input:** Fuel cells require a source of fuel, typically hydrogen, although other fuels like natural gas or methanol can also be used. Hydrogen is the most common fuel for fuel cells because it produces only water and heat as byproducts when it reacts with oxygen.

Electrochemical Reaction: Inside the fuel cell, the fuel (usually hydrogen) is split into protons and electrons through a process called electrolysis. The electrons are forced to flow through an external circuit, creating an electric current. This flow of electrons is what generates electricity.

Oxygen Supply: Oxygen from the air is supplied to the other side of the fuel cell, where it reacts with the protons and electrons to form water (H_2O) as a byproduct. This reaction produces heat, which can be harnessed for various purposes, making fuel cells highly efficient.

Electricity Generation: The electric current produced by the flow of electrons through an external circuit can be used to power electric devices, vehicles, or to charge batteries.

Fuel cells offer several advantages over conventional internal combustion engines and batteries:

High Efficiency: Fuel cells are highly efficient at converting fuel into electricity, typically operating at efficiencies above 50%, which is much higher than internal combustion engines.

Clean Energy: When hydrogen is used as the fuel, the only byproduct is water vapor, making fuel cells a clean and environmentally friendly energy source.

Quiet and Low Emissions: Fuel cell vehicles produce little to no noise and have lower emissions compared to traditional vehicles.

Long Range: Fuel cell vehicles, especially in the context of hydrogen fuel cell cars, can offer a long driving range on a single tank of hydrogen.

Versatility: Fuel cells can be used in a variety of applications, from powering vehicles to providing backup power for buildings and remote locations.

Challenges associated with fuel cells, such as the production and storage of hydrogen, infrastructure for refueling, and cost considerations.

Despite these challenges, fuel cell technology continues to advance and holds promise for a sustainable and clean energy future, particularly in sectors where long-range and rapid refueling are crucial, like transportation and backup power generation

Why do we need fuel cells?


- Fuel cells are a promising and increasingly important technology for a variety of reasons. Here are some key reasons why we need fuel cells:
- **Clean Energy:** Fuel cells offer a clean and environmentally friendly way to generate electricity. When hydrogen is used as the fuel, the only byproduct is water vapor, making fuel cells a zero-emission energy source. This is crucial for addressing climate change and reducing air pollution.
- **Efficiency:** Fuel cells are highly efficient at converting fuel into electricity, often surpassing 50% efficiency. This is significantly higher than the efficiency of many other energy conversion technologies, including internal combustion engines.
- **Reduced Dependence on Fossil Fuels:** While hydrogen fuel cells can use hydrogen produced from natural gas, they can also use hydrogen produced through renewable methods like electrolysis of water using renewable energy sources. This reduces our reliance on fossil fuels for energy production.

- **Versatility:** Fuel cells can be used in various applications, from powering vehicles to providing backup power for buildings and remote locations. Their versatility makes them suitable for a wide range of industries and uses.
- **Long-Range Transportation:** Hydrogen fuel cells are particularly useful in transportation, such as fuel cell vehicles (FCVs). They offer longer driving ranges and shorter refueling times compared to battery electric vehicles (BEVs), making them a viable option for long-range transportation.
- **Grid Resilience:** Fuel cells can provide backup power to critical infrastructure, such as hospitals, data centers, and military installations, ensuring that these facilities remain operational during power outages. This enhances grid resilience and reliability.
- **Reduced Noise Pollution:** Fuel cell-powered vehicles and equipment are quieter than those powered by internal combustion engines, contributing to reduced noise pollution in urban areas.
- **Space Exploration:** Fuel cells have been used in space exploration missions for decades due to their reliability and ability to generate electricity in remote and challenging environments.

- **Decentralized Energy Production:** Fuel cells can be deployed in distributed energy generation systems, reducing the need for extensive centralized power plants and transmission infrastructure. This can enhance energy security and resilience.
- **Hydrogen as an Energy Carrier:** Hydrogen, which is commonly used in fuel cells, can serve as an energy carrier. It can store excess renewable energy and be transported to where it's needed, enabling the integration of renewable energy sources into the grid.
- **Reduction of Greenhouse Gas Emissions:** Fuel cells, when combined with sustainable hydrogen production methods, can play a role in reducing greenhouse gas emissions. They can help decarbonize sectors like transportation, industry, and power generation

- **Technological Innovation:** Research and development in fuel cell technology drive advancements in materials science, engineering, and energy storage, contributing to broader technological progress.
- While fuel cells have many advantages, they also face challenges, including the cost of materials, infrastructure development (e.g., hydrogen refueling stations), and the energy required to produce clean hydrogen. Nevertheless, fuel cells continue to be an important part of the clean energy landscape, especially in sectors where high energy density, long-range operation, and rapid refueling are essential.

CONSTRUCTION




- **Anode**- Negative post of the fuel cell. Conducts the electrons that are freed from the hydrogen molecules so that they can be used in an external circuit. Etched channels disperse hydrogen gas over the surface of catalyst.

- **Cathode**- Positive post of the fuel cell. Etched channels distribute oxygen to the surface of the catalyst. Conducts electrons back from the external circuit to the catalyst. Recombine with the hydrogen ions and oxygen to form water.
- **Electrolyte**- Proton exchange membrane. Specially treated material, only conducts positively charged ions. Membrane blocks electrons.
- **Catalyst**- Special material that facilitates reaction of oxygen and hydrogen. Usually platinum powder very thinly coated onto carbon paper or cloth. Rough & porous maximizes surface area exposed to hydrogen or oxygen. The platinum-coated side of the catalyst faces the PEM.

WORKING

- A fuel cell generates electrical power by continuously converting the chemical energy of a fuel into electrical energy by way of an electrochemical reaction. The fuel cell itself has no moving parts, making it a quiet and reliable source of power. Fuel cells typically utilize hydrogen as the fuel, and oxygen (usually from air) as the oxidant in the electrochemical reaction. The reaction results in electricity, by-product water, and by-product heat.

- When hydrogen gas is introduced into the system, the catalyst surface of the membrane splits hydrogen gas molecules into protons and electrons. The protons pass through the membrane to react with oxygen in the air (forming water). The electrons, which cannot pass through the membrane, must travel around it, thus creating the source of DC electricity.



ADVANTAGES

- Water is the only discharge (pure H₂)
- Higher efficiency than conventional engines.
- Excellent part load characteristics.
- Zero emission.
- Long operating period between failures.
- No rotating parts in the main hard ware components.
- Negligible noise pollution.

DISADVANTAGES

- CO₂ discharged with methanol reform.
- Little more efficient than alternatives.
- Technology currently expensive.
 - Many design issues still in progress.
- Hydrogen often created using “dirty” energy (*e.g.*, coal).
- Pure hydrogen is difficult to handle.

APPLICATIONS

- Can be used as power sources in remote areas.
- Can be used to provide off-grid power supplies.
- Can be applicable in both hybrid and electric vehicles.
- Waste water treatment plant and landfill.
- Cellular phone, laptop and computers.
- Hospitals, credit card centres and police stations.
- Buses, Car, Planes, Boats, Fork lift, Trains
- Vacuum cleaner.
- Telecommunication, MP3 players, etc.

- Fuel cells operate based on electrochemical reactions involving the conversion of fuel and oxidizer into electricity and waste products. The basic chemistry and thermodynamics of a fuel cell can be understood by examining the specific reactions that occur within different types of fuel cells. an overview of the chemistry and thermodynamics of a hydrogen fuel cell, which is one of the most common types, specifically the Proton Exchange Membrane Fuel Cell (PEMFC) .
- **Chemistry and Thermodynamics of a Hydrogen Fuel Cell (PEMFC):**
- **Fuel and Oxidizer:**
 - **Fuel:** Hydrogen gas (H_2).
 - **Oxidizer:** Oxygen gas (O_2) typically from the air.
- **Electrolyte:** In a PEMFC, a solid polymer electrolyte membrane (often made of perfluorosulfonic acid) is used. This membrane allows protons (H^+ ions) to move through it while blocking the passage of electrons (e^-).

- **Anode Reaction (Oxidation):**

- **Chemical Reaction:** At the anode (negative electrode): $\text{H}_2 \rightarrow 2\text{H}^+ + 2\text{e}^-$
- **Thermodynamics:** This reaction involves the splitting of hydrogen molecules into protons and electrons. It is an exothermic reaction, releasing energy.

- **Cathode Reaction (Reduction):**

- **Chemical Reaction:** At the cathode (positive electrode): $\frac{1}{2}\text{O}_2 + 2\text{H}^+ + 2\text{e}^- \rightarrow \text{H}_2\text{O}$
- **Thermodynamics:** This reaction combines oxygen, protons, and electrons to produce water. It is an exothermic reaction.

- **Overall Cell Reaction:**

- **Chemical Reaction:** Combining the anode and cathode reactions, the overall cell reaction is: $\text{H}_2 + \frac{1}{2}\text{O}_2 \rightarrow \text{H}_2\text{O}$
- **Thermodynamics:** This reaction is highly exothermic, releasing a significant amount of energy in the form of heat.

- **Electricity Generation:**

- **Electron Flow:** Electrons released during the anode reaction flow through an external circuit to the cathode, creating an electric current.
- **Proton Flow:** Protons created during the anode reaction pass through the electrolyte membrane to the cathode, where they combine with oxygen and electrons to form water.

- **Energy Efficiency:**

- **Thermodynamic Efficiency:** The overall energy efficiency of a fuel cell is determined by the thermodynamics of the reactions. Hydrogen fuel cells are known for their high thermodynamic efficiency, typically above 50%.
- **Waste Heat:** The heat generated during the exothermic reactions can be harnessed for various purposes, such as heating or providing additional power through combined heat and power (CHP) systems, improving the overall efficiency.

- **Waste Products:**

- The primary waste product of a hydrogen fuel cell is pure water (H_2O), making it environmentally friendly.


- Hydrogen fuel cell, specifically a PEMFC, operates through the electrochemical reactions of hydrogen and oxygen. These reactions are highly efficient, releasing energy in the form of electricity and heat while producing water as the only waste product. The thermodynamics of these reactions play a crucial role in determining the overall efficiency of the fuel cell system.

- The heat of reaction in a fuel cell refers to the amount of heat released or absorbed during the electrochemical reactions that take place within the cell. The heat of reaction is an important consideration in fuel cell design and operation because it affects the overall efficiency and temperature control of the system. The specific heat of reaction varies depending on the type of fuel cell and the reactions involved.
- In a typical hydrogen fuel cell, such as a Proton Exchange Membrane Fuel Cell (PEMFC) or Solid Oxide Fuel Cell (SOFC), there are both exothermic (heat-releasing) and endothermic (heat-absorbing) reactions occurring simultaneously:
- **Exothermic Reactions:**
 - At the anode (negative electrode), hydrogen gas (H_2) is oxidized to produce protons (H^+) and electrons (e^-). This is an exothermic reaction and releases heat.
 - Example: $H_2 \rightarrow 2H^+ + 2e^-$
 - At the cathode (positive electrode), oxygen gas (O_2) combines with protons and electrons to form water (H_2O). This is also an exothermic reaction and releases heat.
 - Example: $\frac{1}{2}O_2 + 2H^+ + 2e^- \rightarrow H_2O$

- **Endothermic Reactions:**
 - In some fuel cells, like the Solid Oxide Fuel Cell (SOFC), there are endothermic reactions that occur within the cell, such as the dissociation of oxygen at high temperatures. These reactions absorb heat.
- The overall heat of reaction is determined by the net effect of these exothermic and endothermic reactions. If the exothermic reactions release more heat than the endothermic reactions absorb, the fuel cell will be exothermic overall, and it will generate excess heat as a byproduct. Conversely, if the endothermic reactions absorb more heat than the exothermic reactions release, the fuel cell will be endothermic overall, and it will require external heating to maintain its operating temperature.
- The heat of reaction in a fuel cell has several implications:

- **Temperature Control:** It influences the operating temperature of the fuel cell. Some fuel cells, like PEMFCs, operate at relatively low temperatures, while others, like SOFCs, operate at high temperatures. Temperature control is critical for the efficiency and performance of the cell.
- **Efficiency:** The heat of reaction affects the overall efficiency of the fuel cell system. Excessive heat generation can lead to thermal losses, reducing the overall efficiency. Conversely, in endothermic fuel cells, additional heat input may be required to maintain the desired temperature.
- **Heat Recovery:** Excess heat generated in exothermic fuel cells can be harnessed for useful purposes, such as heating buildings or providing combined heat and power (CHP) in cogeneration systems, thereby improving overall energy efficiency.
- **Materials and Design:** The choice of materials and the design of the fuel cell stack must take into account the heat generated or absorbed to ensure safe and efficient operation.
- In summary, the heat of reaction in a fuel cell is a crucial factor that influences its operation, efficiency, and temperature control. Proper management of heat is essential to optimize the performance and longevity of fuel cell systems in various applications.


- Fuel cells can be classified into several different types based on the electrolyte material used and the operating temperature. The most common types of fuel cells are:
- Proton Exchange Membrane Fuel Cells (PEMFCs):**
 - Electrolyte:** A solid polymer electrolyte, typically made of a perfluorosulfonic acid membrane.
 - Operating Temperature:** Relatively low, typically between 50°C to 100°C.
 - Applications:** Commonly used in automotive applications because of their fast startup and shutdown times and high power density. They are also used in small-scale stationary power generation.



Electrode reactions take place upon supplying hydrogen to the fuel electrode and oxygen to the air electrode, and thus an electric current can be obtained. At the fuel electrode, the hydrogen is converted into hydrogen ions and electrons.



The hydrogen ions pass through the ion-exchange membrane to reach the opposing air electrode. At the air electrode, the hydrogen ions combine with the electrons, which have passed through the external load circuit and with oxygen supplied to the air electrode in a reaction, which produces water.



Apart from the electrode reactions, a key issue is that for this type of proton exchange membrane, ion conductivity will appear only when the membrane appropriately contains water moisture. It is therefore important to regulate the water content in the membrane by humidifying the reactant gases being supplied. Also, because the ion conductivity depends on the membrane thickness, it should be as thin as the constraints on strength and durability will allow. The operating temperature is limited by the heat resistance of the ion-exchange membrane, though a high temperature is desirable to improve cell characteristics. At present operating temperatures are around 100 °C.

Alkaline Fuel Cells (AFCs):

Electrolyte: Alkaline solution (usually potassium hydroxide) in the form of a liquid electrolyte.


Applications: Historically used by NASA in the Apollo space missions. They are also used in some niche applications, such as in submarines and spacecraft.

- This type of fuel cell was introduced in the early 1960's. As the electrolyte used for this device is aqueous alkaline solution like potassium hydroxide, the procedure for electricity consumption is rather expensive.

It has;

- compressed hydrogen and oxygen fuel.
- potassium hydroxide (KOH) electrolyte.
- ~70% efficiency.
- 150°C - 200°C operating temp.
- 300W to 5kW output requires pure hydrogen fuel and platinum catalyst.

ALKALINE FUEL CELL



Phosphoric Acid Fuel Cells (PAFCs):

Electrolyte: Phosphoric acid in a liquid form is used as the electrolyte.


Applications: PAFCs are used in stationary power generation, such as for cogeneration in industrial settings and as backup power for buildings.

PHOSPHORIC ACID FUEL CELL

- Molten phosphoric acid is the electrolyte used in this type of fuel cell. It operates at high temperature up to 200 degree Celsius. It has an efficiency of up to 55%. This type of fuel cell is most commonly used in commercial cars.

It has;

- phosphoric acid electrolyte.
- 40 - 80% efficiency.
- 150°C - 200°C operating temp.
- 11 MW units have been tested.
- sulphur free gasoline can be used as a fuel.
- The electrolyte is very corrosive.
- Platinum catalyst is very expensive.



Molten Carbonate Fuel Cells (MCFCs):


Electrolyte: A molten carbonate salt mixture, typically lithium potassium carbonate.

Operating Temperature: High, around 650-750°C.

Applications: Suited for large stationary power generation, such as in combined heat and power (CHP) systems for industrial and utility-scale applications. They can use natural gas or biogas as fuel.

- Molten alkaline carbonate like sodium bicarbonate is used as the electrolyte. They can produce high powers up to 100 Mega Watts. Thus they can be used as high power generators. They can also be operated at high temperatures up to 650 degree Celsius. They are not so expensive in production and hence can be used for commercial uses. It has an efficiency of almost 55%.

MOLTEN CARBONATE FUEL CELL



Solid Oxide Fuel Cells (SOFCs):


Electrolyte: A solid ceramic electrolyte, typically made of zirconium oxide or yttrium-stabilized zirconia.

Operating Temperature: High, between 600-1000°C.

Applications: SOFCs are used in a variety of stationary power generation applications, including distributed power generation and auxiliary power units (APUs) for vehicles. They can run on various fuels, including natural gas, hydrogen, and biogas.

- This is one of the most commercially used fuel cell as they have the highest operating life. It has a very high operating temperature of 1,000 degrees Celsius. But other parts of the fuel cell may not be able to withstand at this temperature making it highly unstable. But, when used in a continuous state they can be highly reliable. At high temperatures the device can produce water in the form of steam which can be easily transported through steam turbines to produce more electricity, thus increasing the efficiency of the system. This device is also special in the case where a wide variety of fuels can be used. Most of the petroleum products can be used as the fuel. The electrolyte used in the cell is called yttria stabilized zirconia (YSZ). This electrolyte is good for large scale power generation and has the same characteristics as all the other electrolytes.
- As the device has a very high operating temperature, there are some disadvantages as well. There may be unwanted number of reactions taking place inside the cell due to the high temperature. As a result of these reactions carbon dust and also graphite may be built up on the anode making it insufficient from reacting with the catalyst.

SOLID OXIDE FUEL CELL



- **Solid Oxide Fuel Cells (SOFCs):**
 - **Electrolyte:** A solid ceramic electrolyte, typically made of zirconium oxide or yttrium-stabilized zirconia.
 - **Operating Temperature:** High, between 600-1000°C.
 - **Applications:** SOFCs are used in a variety of stationary power generation applications, including distributed power generation and auxiliary power units (APUs) for vehicles. They can run on various fuels, including natural gas, hydrogen, and biogas.
- **Direct Methanol Fuel Cells (DMFCs):**
 - **Electrolyte:** A solid polymer electrolyte similar to PEMFCs.
 - **Operating Temperature:** Relatively low, similar to PEMFCs.
 - **Applications:** DMFCs are specifically designed to run on methanol, making them suitable for portable and small-scale applications, such as laptop chargers and backup power systems.

- **Bacterial Fuel Cells (BFCs):**
 - **Electrolyte:** Bacteria are used to facilitate the electrochemical reactions.
 - **Operating Temperature:** Typically at ambient temperatures.
 - **Applications:** BFCs are a relatively new and experimental type of fuel cell. They have potential applications in wastewater treatment, bioenergy production, and environmental monitoring.
- These classifications are based on the type of electrolyte and operating conditions. Each type of fuel cell has its own advantages and disadvantages, making it suitable for specific applications. The choice of fuel cell technology depends on factors such as efficiency requirements, fuel availability, and operating conditions.

- In the context of electrochemistry and electrochemical cells, theoretical electrical work and potential are related concepts that describe the energy changes associated with the movement of electrons during a chemical reaction.
- **Theoretical Electrical Work (W):** This refers to the work done by or on an electrochemical system as a result of the movement of electric charge (i.e., electrons) through an external circuit. The theoretical electrical work can be calculated using the formula:
- $W = -nF\Delta E$
 - W is the theoretical electrical work (in joules).
 - n is the number of moles of electrons transferred in the chemical reaction.
 - F is the Faraday constant (approximately 96,485 coulombs per mole of electrons).
 - ΔE is the change in electrical potential (in volts) between the two electrodes of the cell.
- The negative sign in the formula indicates that work is done by the system when electrons flow from the anode to the cathode, as is typical in most electrochemical cells.

- **Electrical Potential (E):** This is a measure of the electric potential energy per unit charge at a specific point in an electrochemical cell. It is also known as voltage. Electrical potential is often measured in volts (V). In an electrochemical cell, there are two key types of potentials:
 - **Electrode Potential (E°):** This is the standard electrode potential of a half-cell when it is in its standard state (usually at 1 M concentration, 1 atm pressure, and 298 K temperature). It is a measure of the tendency of an electrode to gain or lose electrons, and it is used to calculate the cell potential (E_{cell}) for a given redox reaction.
 - **Cell Potential (E_{cell}):** This is the overall electrical potential difference between the two electrodes of an electrochemical cell. It is a measure of the cell's ability to generate electrical work. The cell potential is calculated by subtracting the standard electrode potential of the anode from that of the cathode:
 - $E_{\text{cell}} = E^\circ_{\text{cathode}} - E^\circ_{\text{anode}}$
 - A positive cell potential indicates that the cell can do work and is a spontaneous (favorable) reaction, while a negative cell potential indicates a non-spontaneous (unfavorable) reaction.
- The relationship between theoretical electrical work, electrical potential, and the direction of electron flow is fundamental to understanding how electrochemical cells function. When a cell operates, electrons flow from the anode (where oxidation occurs) to the cathode (where reduction occurs), and this electron flow is associated with the release of electrical energy, which can be harnessed for useful work, such as powering electronic devices or generating electricity in batteries and fuel cells.

- The **theoretical efficiency** of a fuel cell is determined by the thermodynamics of the electrochemical reactions occurring within the cell. It represents the maximum possible efficiency that can be achieved in converting the chemical energy of the fuel into electrical energy, assuming ideal conditions and no losses. The efficiency is typically expressed as a percentage.
- The theoretical efficiency of a fuel cell can be calculated using the Gibbs free energy change (ΔG) associated with the electrochemical reactions taking place in the cell. The Gibbs free energy change is related to the cell potential (E_{cell}) and can be calculated using the formula:
 - $\Delta G = -nFE_{\text{cell}}$
 - Where:
 - ΔG is the Gibbs free energy change (in joules or kilojoules).
 - n is the number of moles of electrons transferred in the chemical reaction.
 - F is the Faraday constant (approximately 96,485 coulombs per mole of electrons).
 - E_{cell} is the cell potential (in volts).

- The theoretical efficiency (η) of the fuel cell can be calculated as:
- $\eta = (\Delta G / \Delta H) \times 100\%$
- Where:
- η is the theoretical efficiency (in percentage).
- ΔG is the Gibbs free energy change.
- ΔH is the enthalpy change associated with the combustion or electrochemical reaction of the fuel (in joules or kilojoules).
- It's important to note that the enthalpy change (ΔH) depends on the specific fuel used and the reaction taking place. For example, in a hydrogen fuel cell, the fuel is hydrogen gas (H_2), and the reaction produces water (H_2O). The enthalpy change for this reaction is known.

- The theoretical efficiency of fuel cells can vary depending on factors such as the type of fuel cell (e.g., PEMFC, SOFC, etc.), the operating conditions, and the specific reactions involved. In practice, actual fuel cell efficiencies are typically lower than the theoretical values due to various losses, including:
 - Activation over potential: Energy losses associated with the need to overcome electrochemical activation barriers.
 - Ohmic losses: Resistance to the flow of ions and electrons within the cell.
 - Mass transport losses: Limitations in the transport of reactants (fuel and oxidizer) to the electrode surface.
 - Heat losses: Energy losses as heat due to the exothermic and endothermic reactions.
- These losses reduce the overall efficiency of a fuel cell system below its theoretical maximum. However, fuel cell technologies are continually being improved to minimize these losses and increase practical efficiency, making them more competitive and environmentally friendly as energy conversion devices.

- An anode is an electrode where an oxidation reaction takes place. The potential of an anode through which a current flows is higher than its equilibrium potential
- A cathode is an electrode where reduction reaction takes place. The potential of a cathode through which a current flows is lower than its equilibrium potential

REFERENCES

Fuel Cells: Principles, Design, and Analysis

Shripad T. Revankar, Pradip Majumdar

Fuel Cell Handbook (Seventh Edition)

By EG&G Technical Services, Inc.

<https://www.slideshare.net/ArvindHeer/fuel-cells-64644787>